

# SOPHO

## iSMobile

DECT Cordless Communications

Handset model C933

- Loudspeaker for handsfree operation
- 60 name/number directory
- Large graphic LCD
- Illuminated display and keyboard
- Light slim-line ergonomic handset: 140 gr/189 cc
- Headset connection
- Built-in silent ring (vibrating)
- Date and time display
- Removable beltclip
- Last number redial (20)
- Voice-mail indication
- Text-message indication
- Missed call log (20)
- Incoming call filter
- Data connection



The handset's extensive features meet the demanding business user's every need. They include advanced control of incoming calls, a large directory and support of E2-based text messaging. The C933 is an attractively designed, state-of-the-art, digital cordless telephone that complies with ETSI DECT-GAP/CAP and E2 standards. The C933 provides secure communication through encryption techniques.

The handset has a large, illuminated, alphanumeric display showing the called number/name, directory dialling from a 60-entry memory and easy-to-use menu programming. The built-in loudspeaker and headset connection allow for hands-free operation with excellent sound quality.



# PHILIPS

*Let's make things better.*

# Technical Data

## HANDSET FEATURES

- 9 hours talk time
- 100 hours standby
- Loudspeaking mode for handsfree operation
- Built-in vibrator for silent alert
- Illuminated display and key-board
- Directory dialling from 60-name phonebook (with automatic alpha-sort)
- Calling Line Identification Presentation (CLIP) of the last 16 digits
- Easy-to-use menu programming
- On-hook number preparation with correction option (down-key)
- Last number redial (20)
- Recall (PBX Enquiry)
- 10 subscriptions with manual or automatic selection
- Automatic encryption
- Microphone mute
- Keypad lock
- GAP/CAP/E2 compliant
- 10 Languages supported
- Adjustable volume for ear-piece, loudspeaker and headset (6 steps)
- Removable beltclip
- Date and time display\*
- Call duration display\*
- Adjustable ringer volume (6 steps menu selection)
- Ringer melodies (30)
- Ringer mute/trembler mute
- Quick dial (9 numbers)
- Last number redial (20)
- Missed Call log (20)
- Text messaging (10)
- Message length 160 characters
- Date time stamp on logged calls and messages\*
- Serial Data link
- Headset connection
- Incoming call filter
- Call Reject
- Alarm function (watch)\*
- Large LED ring indicator

## FEATURES SUPPORTED WITH SOPHO iS3000 PBX

- All PBX features via DTMF dialling
- Alpha-numeric message display during ring (20 characters scrolling)
- Alpha-numeric calling name display (14 characters scrolling)

For further information please contact your local Philips office or:

Philips Business Communications  
P.O. Box 32,  
1200 JD Hilversum,  
The Netherlands  
Tel. (int.) +31 35 689 91 11  
Fax +31 35 689 14 50  
Internet: <http://www.sopho.philips.com>

## LCD DISPLAY

Graphic LCD (96 x 60 pixels) with 5 lines of 16 characters, one line for icons.

8 icons for:

- Field strength, 4 steps
- Battery level, 4 steps
- Voicemail indication
- Text message (normal/urgent)
- On/Off hook
- Buzzer off
- Call filter active
- Alarm clock active

## KEYS

- On/Off-hook key
- Soft key (2)
- Key-pad 0...9, # and \*
- Clear
- Recall
- Up/down
- Volume up/down
- Power on/off

## MESSAGING FUNCTIONS

Text messaging is available in combination with the iS3000 applications.

Messages can be received during any call state of the handset.

- Receive: 160 characters\*
- Type: Normal/Urgent
- Storage: 10 messages
- Scroll message list
- Time and date stamp\*
- Message read indication
- Urgent message indication
- Message delete
- Message waiting

## WARNING INDICATORS

Battery discharged  
New message  
Out of coverage  
Alarm clock

## LED INDICATOR

Incoming call/incoming message/recharge

## MENU LANGUAGES

Dutch, English, German, Italian, Spanish, French, Swedish, Danish, Portuguese, Norwegian

## POWER SUPPLY

2 x AAA (1.2 V/700 mAh) NiMH

## CHARGER

The desktop charger is powered through a separate mains adapter.

Mains: 230 V/50 Hz

Charging current: 7V DC/150 mA

Mainsplug: Euro or UK or Taiwan

## COMPLIANCE

ETSI 300 329

EN 60950

DECT CTR6, CTR 10, CTR 22

ITU E.161 (key-pad)

## PHYSICAL CHARACTERISTICS

### Dimensions

Handset: 143 x 51 x 26 mm (189 cc)

Charger: 90 x 83 x 66 mm

Data charger: 62 x 78 x 97,5 mm

Charger rack: 130 x 560 x 65 mm

### Weight

Handset: 140 gr.

### Temperature range

Operation: 0 to +40oC

Storage: -25o to +70oC

### Relative humidity

Operation: Up to 95 % RH at 40oC

Storage: Up to 95 % RH at 40oC

### Protection

IP50

### Radio Frequency & power

1880 - 1895mHZ , < 250 mW

### Range

50 m max. Indoor range\*\*

300 m max. Outdoor range\*\*

### Colour and Finishing

Silver/dark blue

### Package contents

Handset

2 AAA NiMH batteries

Desktop charger

Belt-clip

### Accessories (optional)

Headset

Application CD-ROM

Serial data cable

Desktop data charger

Protective cover

Carrying case

Charging rack

Note:

\* PBX SW release dependent

\*\* The range of the DECT telephones depends on the environment and the presence of obstacles